



The Chemical Company

Safety data sheet

KURE N SEAL VOC COMPLIANT

Revision date : 2009/04/20
Version: 1.0

Page: 1/6
(30367870/SDS_GEN_US/EN)

1. Substance/preparation and company identification

Company
BASF Construction Chemicals
100 Campus Drive
Florham Park, NJ 07932

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
64742-95-6	5.0 - 10.0 %	solvent naphtha

3. Hazard identification

Emergency overview

WARNING: COMBUSTIBLE LIQUID AND VAPOR.
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
MAY BE HARMFUL IF SWALLOWED.
REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.
Overexposure may cause CNS depression including headache, dizziness, nausea and loss of consciousness.
Keep container tightly closed.
Avoid all sources of ignition: heat, sparks, open flame.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

No data available.

Irritation:

The product has not been tested. The statement has been derived from the properties of the individual components.

Potential environmental effects

Aquatic toxicity:

At the present state of knowledge, no negative ecological effects are expected.
There is a high probability that the product is not acutely harmful to aquatic organisms.
The product has not been tested. The statement has been derived from products of a similar structure and composition.

Safety data sheet

KURE N SEAL VOC COMPLIANT

Revision date : 2009/04/20
Version: 1.0

Page: 2/6
(30367870/SDS_GEN_US/EN)

4. First-aid measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

5. Fire-fighting measures

Flash point: 42.22 °C
Lower explosion limit: 0.9 %(V)
Upper explosion limit: 7 %(V)

Suitable extinguishing media:

carbon dioxide, dry extinguishing media, water fog

Hazards during fire-fighting:

carbon monoxide, carbon dioxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

Remove product from areas of fire, or otherwise cool containers with water in order to avoid pressure build up due to heat. The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Sources of ignition should be kept well clear. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Safety data sheet

KURE N SEAL VOC COMPLIANT

Revision date : 2009/04/20

Version: 1.0

Page: 3/6

(30367870/SDS_GEN_US/EN)

Cleanup:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

7. Handling and storage

Handling

General advice:

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Keep away from heat. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

Storage

General advice:

Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Store protected against freezing.

Storage incompatibility:

General: Segregate from metals. Segregate from lyes. Segregate from oxidants. Segregate from foods and animal feeds.

Temperature tolerance

Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures below: 32 °F

The packed product must be protected from temperatures below the indicated one.

8. Exposure controls and personal protection

Personal protective equipment

Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

Safety data sheet

KURE N SEAL VOC COMPLIANT

Revision date : 2009/04/20

Version: 1.0

Page: 4/6

(30367870/SDS_GEN_US/EN)

9. Physical and chemical properties

Form:	liquid	
Odour:	mild, solvent-like	
Colour:	white	
pH value:		Unspecified
Boiling point:	153.33 - 171.11 °C	
Vapour pressure:		No data available.
Density:	1.004 g/cm ³	
Vapour density:		Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):		No data available.
Viscosity, dynamic:		No data available.

10. Stability and reactivity

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Decomposition products:

Thermal decomposition products: carbon oxides

11. Toxicological information

Chronic toxicity

Carcinogenicity:

Information on: solvent naphtha

The substance caused cancer in animal studies.

Other information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.

12. Ecological information

Environmental toxicity

Other ecotoxicological advice:

Ecological data are not available.

13. Disposal considerations

Waste disposal of substance:

Recommendations: Use excess product in an alternate beneficial application.

Safety data sheet

KURE N SEAL VOC COMPLIANT

Revision date : 2009/04/20

Version: 1.0

Page: 5/6

(30367870/SDS_GEN_US/EN)

Dispose of in accordance with national, state and local regulations.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US

released / listed

OSHA hazard category:

Chronic target organ effects reported, Combustible Liquid

SARA hazard categories (EPCRA 311/312): Acute, Chronic, Fire

State regulations

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

16. Other information

HMIS III rating

Health: 1

Flammability: 2

Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

BASF Construction Chemicals

bcc_prps@basf.com

Safety data sheet

KURE N SEAL VOC COMPLIANT

Revision date : 2009/04/20

Version: 1.0

Page: 6/6

(30367870/SDS_GEN_US/EN)

END OF DATA SHEET