

MATERIAL SAFETY DATA SHEET



PROSOCO, Inc.

I PRODUCT IDENTIFICATION

MANUFACTURER'S NAME AND ADDRESS: PROSOCO, Inc.
3741 Greenway Circle
Lawrence, KS 66046

EMERGENCY TELEPHONE NUMBERS:
8:00 AM – 5:00 PM CST Monday-Friday: 785/865-4200
NON-BUSINESS HOURS (INFOTRAC): 800/535-5053

PRODUCT TRADE NAME: Sure Klean® Weather Seal Blok-Guard® & Graffiti Control II

II HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS NO.	ACGIH TLV/TWA	OSHA PEL/TWA
Silicone emulsion	*	NE	NE

Ethyl Alcohol is formed upon contact with water or humid air and evolves slowly during curing. TLV/PEL = 1000 ppm.

*Specific chemical identity withheld as Trade Secret in accordance with OSHA regulations.

III PHYSICAL DATA

	SPECIFIC GRAVITY	SOLUBILITY IN WATER	APPEARANCE AND ODOR
Blok-Guard® & Graffiti Control II* *Typical	1.00	Yes	Milky white liquid, slight odor

IV FIRE AND EXPLOSION HAZARD DATA

EMERGENCY OVERVIEW

Sure Klean® Weather Seal Blok-Guard® & Graffiti Control II is a milky white liquid. Contact with the eyes or skin may result in irritation. Mist inhalation may cause irritation. Always wear appropriate personal protective equipment when using this product. Product evolves ethyl alcohol during curing that can accumulate in confined work areas. Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines. Do not repackage.

FLASH POINT (METHOD): >212°F (ASTM D 3278)

FLAMMABLE LIMITS: Not determined

EXTINGUISHING MEDIA: Use dry chemical, foam or water spray.

SPECIAL FIRE FIGHTING PROCEDURES: None.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Although there is no flash point, flammable vapors of ethyl alcohol may accumulate in the headspace of the container when storage times of six months are exceeded.

V HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE: Skin, eyes, ingestion, inhalation.

CARCINOGEN INFORMATION: Not listed (OSHA, IARC, NTP).

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: No applicable information found.

EFFECTS OF OVEREXPOSURE: Irritation of the eyes. Long term, occupational overexposure by inhalation may cause injury to the liver.

EYE CONTACT: Direct contact may cause moderate irritation.

SKIN CONTACT: May cause moderate irritation.

INHALATION: No toxic effects are expected under normal use conditions. Inhalation of aerosols may cause respiratory irritation. Alcohol will evolve during curing and can cause drowsiness and other central nervous system effects. Concentrations should be minimal with appropriate ventilation. Long term occupational exposures may cause damage to the liver.

INGESTION: Not expected in industrial/commercial use. On hydrolysis, this product has the potential to evolve potentially harmful ethyl alcohol. May cause dizziness, drowsiness, confusion or loss of coordination.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: If in eyes, flush with large amounts of water for 15 minutes, holding eyelids apart to ensure flushing of the entire eye surface. Get medical attention.

SKIN CONTACT: Wash exposed area with soap and water. Remove contaminated clothing. If persistent irritation occurs, get medical attention. Launder contaminated clothing before reuse.

INHALATION: No respiratory effects anticipated. Remove to fresh air. Get medical attention if ill effects persist.

INGESTION: Get immediate medical attention. If vomiting occurs, keep head below hips to prevent liquid from entering lungs. Never give anything by mouth to an unconscious person.

VI REACTIVITY DATA

STABILITY: Relatively non-reactive, but will hydrolyze slowly at ambient temperatures to form ethanol.

CONDITIONS TO AVOID: None.

INCOMPATIBILITY (MATERIALS TO AVOID): Water, moisture or humid air can cause hazardous vapors to form. Do not repackage, dilute, or alter this product.

HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: After long periods of time, small amounts of hydrogen gas and ethanol may be formed in the container headspace. Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Nitrogen oxides. Hydrogen. Formaldehyde.

VII SPILL OR LEAK PROCEDURES

SPILL, LEAK, WASTE DISPOSAL PROCEDURES: Wear appropriate protective safety equipment. Floors may be slippery; care should be exercised to avoid falls. Contain and keep from sewers and surface waters.

WASTE DISPOSAL METHODS: Dispose of in accordance with federal, state and district regulations. This material as supplied is not classified as a hazardous waste by USEPA RECRA criteria. Federal regulation prohibits disposal of liquid materials of any kind in a sanitary landfill. Solidify cleanup residuals before disposal. As local and state regulations may vary, consult with appropriate state and local regulatory agencies or the sanitary landfill operator to ascertain proper disposal procedures.

Empty containers must not be reused. Drain all liquid possible from the container before disposal in a sanitary landfill.

VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear a NIOSH approved dust/mist respirator as necessary to avoid unnecessary inhalation of wind drift during application. Ventilate interior spaces during curing as minute quantities of ethanol may be evolved.

VENTILATION: Mechanical local exhaust at point of use.

PROTECTIVE CLOTHING: Wear protective clothing such as long sleeved work shirt and pants, work boots, and rubber gloves as needed to avoid skin contact. Do not allow clothing to become saturated with product. If work practices cannot be adjusted to avoid excess clothing saturation, splash resistant or Tyvek clothing and boots may be required.

PROTECTIVE GLOVES: Chemically resistant gloves such as nitrile, rubber, or PVC may be used.

EYE PROTECTION: Safety glasses with side shields are recommended. Splash resistant goggles or a face shield should be used prevent eye contact where wind-drift and excess atomization can pose a risk

OTHER PROTECTIVE EQUIPMENT: Access to an eyewash is recommended. Personal protective clothing and use of equipment must be in accordance with 29 CFR 1910.133 and 29 CFR 19120. 132.

IX SPECIAL PRECAUTIONS

WORK PRACTICES: Proper work practices and planning should be utilized to avoid contact with workers, passersby, and non-masonry surfaces. Do not atomize during application. Beware of wind drift. See the Product Data sheet and label for specific precautions to be taken during use. Wash hands before breaks and at the end of a shift.

This product will continue to evolve vapor during drying and ethyl alcohol during curing. Continue ventilation as needed during curing. Curing is complete in 3-5 days.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Wear appropriate safety equipment and clothing. Do not get in eyes, on skin, or on clothing. Do not take internally. Avoid breathing mist. Never touch face with hands or gloves that may be contaminated with this product.

Store in a cool, dry, well-ventilated place. Keep containers tightly closed when not dispensing product. **Keep from freezing.** Use care around spilled material because it will be slippery.

OTHER PRECAUTIONS: None known.

X REGULATORY INFORMATION

SHIPPING: This product is not regulated for domestic or international shipment.

NATIONAL MOTOR FREIGHT CLASSIFICATION: #33880 sub 2

SARA 313 REPORTABLE:

CHEMICAL NAME	CAS	UPPERBOUND CONCENTRATION % BY WEIGHT
NA	NA	NA

CALIFORNIA PROPOSITION 65: No listed materials are known to be present in this product.

HMS: 2,1,0,X

AIM VOC Compliance Status: Complies with all known federal, state and district AIM VOC standards.

XI OTHER

MSDS Status: **Date of Revision:** May 14, 2009
For Product Manufactured After: December 20, 2004
Changes: No changes. Regulatory review.
Item #: 40193
Approved By: Regulatory Department

DISCLAIMER:

The information contained on the Material Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. **PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described.** This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

DATE OF PREPARATION: May 14, 2009