



MATERIAL SAFETY DATA SHEET

Sika Grout 212

HMIS

HEALTH	*2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	E

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 10/27/2005

Product Name: Sika Grout 212
CAS Number: Not Established
Chemical Family: Cementitious Grout
MSDS Number: 3757
Product Code: 0525540

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
CEMENT, PORTLAND	65997-15-1	
SILICA, QUARTZ	14808-60-7	

3. Hazards Identification

Eye Hazards

May cause eye irritation.

Skin Hazards

Product becomes alkaline when exposed to moisture. May cause a reversible inflammatory effect on skin or tissue at the site of contact.

Ingestion Hazards

May be harmful if swallowed.

MATERIAL SAFETY DATA SHEET

Sika Grout 212

3. Hazards Identification - Continued

Inhalation Hazards

Breathing dust may cause nose, throat or lung irritation. Respirable crystalline silica can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel. If victim is fully conscious, give one or two cups of water or milk to drink. Seek medical attention immediately.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration, seek medical attention.

5. Fire Fighting Measures

Flash Point: >200 °F

Autoignition Point: N/AV °F

Fire And Explosion Hazards

None known

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO₂.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Shovel or sweep up material into suitable containers, taking care to minimize dust. Dampen if necessary to control dust. Vacuum clean dust with equipment fitted with High Efficiency Particulate Air (HEPA) filters.

7. Handling And Storage

Handling And Storage Precautions

Keep containers tightly closed.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use of a system of local and/or general exhaust is recommended to keep employee below applicable exposure limits. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

MATERIAL SAFETY DATA SHEET

Sika Grout 212

8. Exposure Controls/Personal Protection - Continued

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

Lab coat or other work clothing to prevent skin exposure (Long sleeve shirt and long pants). Launder before reuse.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Ingredient(s) - Exposure Limits

CEMENT, PORTLAND

ACGIH TLV-TWA - 10 mg/m³

OSHA PEL -TWA - 15 mg/m³ (total dust)

OSHA PEL - TWA - 5 mg/m³ (respirable dust)

SILICA, QUARTZ

ACGIH TLV-TWA 0.05 mg/m³

OSHA PEL-TWA 30/%SiO₂+2 mg/m³

OSHA PEL-TWA 10/%SiO₂+2 mg/m³

OSHA PEL-TWA 250/%SiO+5 mppcf

9. Physical And Chemical Properties

Appearance

Gray Powder

Odor

Product is odorless. Faint ammonia like smell may be present during curing.

Chemical Type: Mixture

Physical State: Solid

Melting Point: N/AV °F

Boiling Point: N/AV °F

Specific Gravity: 2.7-3.0

Percent Volatiles: N/AV

Percent VOCs: 0%

Packing Density: N/AV

Vapor Pressure: N/AV

Vapor Density: N/AV

Solubility: Negligible

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

Contact of silica with powerful oxidizing agents such as fluorine, chlorine, trifluoride, manganese trioxide, oxygen difluoride, may cause fires. Upon direct contact with water, material will harden.

Incompatible Materials

None Known

MATERIAL SAFETY DATA SHEET

Sika Grout 212

10. Stability And Reactivity - Continued

Hazardous Decomposition Products

Silica will dissolve in hydrofluoric acid and produce a corrosive gas - silicon tetrafluoride.

11. Toxicological Information

Ingredient(s) - Carcinogenicity

SILICA, QUARTZ

NTP - Listed On The National Toxicology Program

Listed In The IARC Monographs

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Proper Shipping Name

Not regulated by the USDOT.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard

Chronic Health Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

State Regulations

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

Ingredient(s) - State Regulations

SILICA, QUARTZ

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

16. Other Information

HMIS Rating

Health: *2

Fire: 0

Reactivity: 0

MATERIAL SAFETY DATA SHEET

Sika Grout 212

16. Other Information - Continued

HMIS Rating - Continued

PPE: E

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supercedes A Previous MSDS Dated: 05/12/2004

Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000