Material Safety Data Sheet

# TREMCO.

# TREMFLEX 834 LIMESTONE

Version 1.1 REVISION DATE: 09/01/2006 Print Date 09/11/2006

## **SECTION 1 - PRODUCT IDENTIFICATION**

Trade name Product code : TREMFLEX 834 LIMESTONE : 9418054323

: (216) 292-5000 8:30 - 5:00 EST

: (216) 765-6727 8:30 - 5:00 EST

: Tremco Incorporated 3735 Green Road Cleveland, OH 44122

COMPANY

Telephone Emergency Phone:

Product use

: Sealant

# **SECTION 2 - HAZARDS IDENTIFICATION**

### **Emergency Overview**

Limestone. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

After Hours: Chemtrec 1-800-424-9300

## Acute Potential Health Effects/ Routes of Entry

Inhalation:May cause slight irritation to the respiratory system.Eyes:Slightly irritating.Ingestion:May cause irritation to the mouth, throat and stomach.Skin:Irritant effect may be delayed.

## **Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

### **Chronic Health Effects**

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

## **SECTION 3 - PRODUCT COMPOSITION**

| 40.0 - 70.0<br>15.0 - 40.0<br>15.0 - 40.0<br>3.0 - 7.0<br>1.0 - 5.0 |        |
|---|--------|
| 15.0 - 40.0<br>3.0 - 7.0<br>1.0 - 5.0                               |        |
| 3.0 - 7.0<br>1.0 - 5.0  |        |
| 1.0 - 5.0   |        |
|   |        |
| 10 50   |        |
| 1.0 - 5.0   |        |
| - <1.0  |        |
|   |        |
|   |        |
|   |        |
|   | - <1.0 |



# TREMFLEX 834 LIMESTONE

Version 1.1 REVISION DATE: 09/01/2006 Print Date 09/11/2006

## SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

| Inhalation | : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. |
|------------|--|
| <b>–</b>   |  |

Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.

Skin contact : Wash with water. If irritation, rash or other disorders develop, get medical attention immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

# **SECTION 5 - FIRE FIGHTING MEASURES**

| Flash point<br>Method<br>Lower explosion limit | : | Not available.<br>Not available.<br>Not available.   |
|--|---|--|
| Upper explosion limit                          | : | Not available.   |
| Autoignition temperature                       | : | Not available.   |
| Extinguishing media                            | : | This product is not expected to burn under normal conditions of use.Use that which is appropriate to the surroundings. |
| Hazardous combustion<br>products               | : | Smoke, fumes.  |
| Protective equipment for<br>firefighters       | : | Not applicable. Product is not expected to burn.   |
| Fire and explosion conditions                  | : | This product not expected to ignite under normal conditions of use.  |

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal. Keep out of water courses.

## **SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not use in confined or poorly ventilated areas. Store in sealed containers in a dry, ventilated warehouse location above freezing.

# **SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### Personal protection equipment

| Respiratory protection | : | Not required under normal conditions of use. |
|------------------------|---|--|
| Hand protection        | : | Protect hands with impervious gloves.        |
| Eye protection         | : | Use safety glasses if eye contact is likely. |
|                        |   |  |

n RPM Company



# TREMFLEX 834 LIMESTONE

Version 1.1

**REVISION DATE: 09/01/2006** 

Print Date 09/11/2006

| Protective measures  | : | Use professional judgment in the selection, care, and use. Other equipment not normally required. |
|----------------------|---|---|
| Engineering measures | : | General ventilation is sufficient.Use local exhaust when the general ventilation is inadequate.   |

### **Exposure Limits**

| Chemical Name         | CAS Number | Regulation | <u>Limit</u> | <u>Form</u>           |
|-----------------------|------------|------------|--------------|-----------------------|
| Calcium Carbonate     | 1317-65-3  | OSHA PEL:  | 5 mg/m3      | Respirable fraction.  |
| (Limestone)           |            | OSHA PEL:  | 15 mg/m3     | Total dust.           |
|                       |            | ACGIH TWA: | 3 mg/m3      | Respirable particles. |
|                       |            | ACGIH TWA: | 10 mg/m3     | Inhalable particles.  |
|                       |            | OSHA TWA:  | 15 mg/m3     | Total dust.           |
|                       |            | OSHA TWA:  | 5 mg/m3      | Respirable fraction.  |
| Titanium dioxide      | 13463-67-7 | ACGIH TWA: | 10 mg/m3     |                       |
|                       |            | OSHA PEL:  | 15 mg/m3     | Total dust.           |
|                       |            | OSHA TWA:  | 15 mg/m3     | Total dust.           |
|                       |            | OSHA TWA:  | 5 mg/m3      | Respirable fraction.  |
| Crystalline Silica    | 14808-60-7 | ACGIH TWA: | 0.05 mg/m3   | Respirable fraction.  |
| (Quartz)/ Silica Sand |            | OSHA TWA:  | 0.1 mg/m3    | Respirable.           |
|                       |            | OSHA TWA:  | 0.3 mg/m3    | Total dust.           |
|                       |            | OSHA PEL:  | 15 mg/m3     | Total dust.           |
|                       |            | OSHA PEL:  | 5 mg/m3      | Respirable fraction.  |
|                       |            |            |              |                       |

# SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| Form                | : Non-sag gunnable paste                      |
|---------------------|---|
| Color               | : Limestone                                   |
| Odor                | : Acrylate                                    |
| рН                  | : Not available.                              |
| Vapour pressure     | : Not available.                              |
| Vapor density       | : Heavier than air                            |
| Melting point/range | : Not available.                              |
| Freezing point      | : Not available.                              |
| Boiling point/range | : Not available.                              |
| Water solubility    | : Miscible                                    |
| Specific Gravity    | : 1.4567                                      |
| % Volatile Weight   | : 20 %  |
| ECTION 10 - REACTIV | ITY / STABILITY                               |
| Substances to avoid | : Oxidizing agents.Strong acids.Strong bases. |
|                     |   |
|                     |   |

Material Safety Data Sheet



# TREMFLEX 834 LIMESTONE

Version 1.1 REVISION DATE: 09/01/2006 Print Date 09/11/2006

## SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available

## **SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

## SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

## SECTION 14 - TRANSPORTATION / SHIPPING DATA

### TDG / DOT Shipping Description:

NOT REGULATED

## **SECTION 15 - REGULATORY INFORMATION**

#### North American Inventories:

All components are listed or exempt from the TSCA inventory. This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

### U.S. Federal Regulations:

| -  |   |            |
|--|---|------------|
| SARA 313 Components  | : None present or none present in regulated quant | tities.    |
| SARA 311/312 Hazards   | : Acute Health Hazard<br>Chronic Health Hazard    |            |
| OSHA Hazardous Components  | :   |            |
| Calcium Carbonate (Limestone)<br>Titanium dioxide<br>Crystalline Silica (Quartz)/ Silica | 13463-67-7  |            |
| OSHA Status: Considered<br>hazardous based on the<br>following criteria:                 | : Irritant  |            |
| OSHA Flammability  | : Not Regulated                                   |            |
| Regulatory VOC (less water and<br>exempt solvent)  | d : 11 g/l  |            |
| VOC Method 310   | : 0%  |            |
| Chemical is listed as an IARC, N<br>Crystalline Silica (Quartz)/ Silica                  | TP, OSHA, or ACGIH Carcinogen:<br>Sand 14808-60-7 |            |
| An RPM Company   | 4/6   | 9418054323 |



Print Date 09/11/2006

# **TREMFLEX 834 LIMESTONE**

Version 1.1 **REVISION DATE: 09/01/2006** 

**U.S. State Regulations:** 

| MASS RTK Components   | : Calcium Carbonate (Limestone)<br>Titanium dioxide   | 1317-65-3<br>13463-67-7  |
|---|---|--|
| Penn RTK Components   | : Calcium Carbonate (Limestone)<br>Acrylic polymer<br>Water<br>White mineral oil<br>Titanium dioxide  | 1317-65-3<br>NJ TSRN# 51721300-5277P<br>7732-18-5<br>8042-47-5<br>13463-67-7               |
| NJ RTK Components   | <ul> <li>Calcium Carbonate (Limestone)<br/>Acrylic polymer<br/>Water</li> <li>White mineral oil</li> <li>Dipropylene glycol dibenzoate</li> <li>Crystalline Silica (Quartz)/ Silica Sand</li> </ul> | 1317-65-3<br>NJ TSRN# 51721300-5277P<br>7732-18-5<br>8042-47-5<br>27138-31-4<br>14808-60-7 |
| Chemicals known to the St<br>14808-60-7<br>1333-86-4<br>140-88-5<br>50-00-0 | ate of California to cause cancer birth defects ar<br>Crystalline Silica (Quartz)/ Silica Sand<br>Carbon Black<br>Ethyl Acrylate<br>Formaldehyde  | nd/or other reproductive harm:   |

## **SECTION 16 - OTHER INFORMATION**

#### **HMIS Rating :**

| Health       | 2 |
|--------------|---|
| Flammability | 1 |
| Reactivity   | 0 |
| PPE          |   |
|              |   |

0 = Minimum1 = Slight2 = Moderate 3 =Serious 4 = Severe

#### Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

#### Prepared by: Rich Mikol

## Legend

| Legena  |                        |   |
|---|------------------------|---|
| ACGIH - American Conference of Governmental                 | Hygienists             | PEL - Permissible Exposure Limit                            |
| CERCLA - Comprehensive Environmental Respo<br>Liability Act | nse, Compensation, and | RCRA - Resource Conservation and Recovery Act               |
| DOT - Department of Transportation                          |                        | RTK - Right To Know   |
| DSL - Domestic Substance List                               |                        | SARA - Superfund Amendments and Reauthorization Act         |
| EPA - Environmental Protection Agency                       |                        | STEL - Short Term Exposure Limit                            |
| HMIS - Hazardous Materials Information System               |                        | TLV - Threshold Limit Value                                 |
| IARC - International Agency for Research on Car             | icer                   | TSCA - Toxic Substances Control Act                         |
| MSHA - Mine Safety Health Administration                    |                        | TWA - Time Weighted Average                                 |
| NDSL - Non-Domestic Substance List                          |                        | V - Volume  |
| NIOSH - National Institute for Occupational Safet           | y and Health           | VOC - Volatile Organic Compound                             |
| NTP - National Toxicology Program                           |                        | WHMIS - Workplace Hazardous Materials Information<br>System |
| OSHA - Occupational Safety and Health Administ              | ration                 |   |
| An RPM Company  | 5/6                    | 9418054323  |

Material Safety Data Sheet

# TREMFLEX 834 LIMESTONE

Version 1.1 REVISION DATE: 09/01/2006



Print Date 09/11/2006