

Flashing and Reglets

Textroflash™ Flashing



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

TeXtroflash™ Flashing

Thru-Wall / Surface-Mount Flashing

A 40-mil thick, non-asphalt composite membrane with a proprietary clear adhesive. This adhesive is factory-laminated to polyethylene sheeting, yielding a flexible membrane that is suitable for application to masonry, concrete, steel, gypsum and wood.

Patents Pending

- Asphalt-free composition will not drool when exposed to UV or heat.
- Corners easily formed on site. Laps easily, just press at overlap.
- Resists tearing and slicing.
- UV-resistant for up to 90 days.
- Now made from 45% Recycled Material.

Technical Data:

- Tensile Strength - **ASTM D412C** 6,242 psi
- Elongation - **ASTM D412C** 16%
- Puncture Resistance - **ASTM E154** 331.8 lbf.
- Water Absorption - **ASTM D1970** 5.544%
- Peel Strength of Adhesive bonds - **ASTM D903** 8.6 lbf/in

Width (rolls are 75 ft. long)

- 12" 16" 18" 20"
 24" 32" 36" Other

Stainless Steel Drip Plate

- 1 1/2" 3" Other _____

Flex-Flash® Drip Edge

- 1 1/2" 3" Other _____

Termination Bar

- T1 Termination Bar
 Stainless Steel (Type 304) Aluminum Plastic
 T2 Termination Bar
 Stainless Steel (Type 304) Aluminum

Mastic & Primer

- H&B 1-Quart Mastic Tube
 H&B Primer 36 (5 gal. pail)
 H&B Mastic (5 gal. pail)