



Since 1915
Tucker
 W. L. TUCKER SUPPLY COMPANY, INC.
 "The Best Names In Construction Are Under Our Roof!"

2800 Second St.
 Cuyahoga Falls
 OH 44221

WWW.WLTUCKER.COM / CALL: 330.928.2155

Foil-Grip™ 1402

Indoor/Outdoor



HUNTER
 CONTINUOUS INSULATION

FOIL-GRIP 1402 is a pressure sensitive, 40-year cycle, general purpose rolled sealant. It provides an instant water resistant grip to most surfaces including Hunter Xci polyiso products.

PART NUMBERS

304093	1 Case w/ (24) 2" x 100' Rolls (Non-printed)
304094	1 Case w/ (16) 3" x 100' Rolls (Non-printed)
304095	1 Case w/ (12) 4" x 100' Rolls (Non-printed)
304096	1 Case w/ (8) 6" x 100' Rolls (Non-printed)
304083	1 Roll 36" x 100' (Non-printed)
304099	1 Case w/ (24) 2" x 100' Rolls (Printed)
304100	1 Case w/ (16) 3" x 100' Rolls (Printed)

TECHNICAL DATA

Appearance	Mill finish aluminum substrate with gray adhesive/sealant
Backing	Aluminum
Thickness	17 mils
Sealant Material	Modified butyl
Peal Strength	16 lbs. per linear inch
Tensile Strength	955 psi avg.
Elongation	560% avg.
Flexibility	Excellent, no cracking
Bonding Time	Instant high tack, full bond 24 hours
Time to Test	Immediate
Service Temperature	-20°F to 200°F
Weather Resistance	Passes 2000 hours QUV (When tested in accordance with ASTM G53)
Mildew Resistance	Mold & mildew resistant
VOC	0 g/l
Pressure Classes	SMACNA ½, 1, 2, 3, 4, 6 and 10 inches w.g.
Seal Classes	SMACNA A, B, C
Packaging	100-ft. rolls in 2, 3, 4, 6 and 36-inch widths 400 ft. ² per case

SPECIFICATION/STANDARDS COMPLIANCE

Property	Method	Results
VOC Limitation	SCAQMD Rule 1168	Pass
City of Los Angeles Approval RR#8069		Pass

APPLICATION

Temperature	35°F to 110°F (1.7°C to 44°C)
Method	Cut desired length, peel off release liner, apply. Removal or repositioning may damage tape and surface. Overlap at ends. Use squeegee with heavy pressure to assure complete contact.
Preparation	Surface must be dry and free of dirt, oil and grease.
Clean Up	UN-TACK™ or Solvent (Use safe handling practices.)

STORAGE

Temperature	35°F to 110°F (1.7°C to 44°C) DO NOT FREEZE
Shelf Life	24 months
Flammability	Non-flammable

CLASSIFIED
US

UNDERWRITERS LABORATORIES INC.®
 CLASSIFIED
 GENERAL USE TAPES

SURFACE BURNING CHARACTERISTICS
 773S
*Applied to inorganic reinforced Cement Board

FLAME SPREAD20
 SMOKE DEVELOPED40

*Tested in two 3-inch (76 mm)-wide longitudinal strips 8-inches (203 mm) on center. (Tape coverage: 30% of the exposed test sample area.)

PRECAUTIONS

Surfaces must be clean and free of moisture and contamination. Do not apply this product in areas where temperatures will exceed 200°F. Keep out of the reach of children. Review MSDS for safety information prior to use. DO NOT use where acidic or alkaline chemicals are present (ie., lab fume hood, vents, etc.)

For Industrial Professional Use Only.



Manufactured by CCW.