


WWW.WLTUCKER.COM

CALL: 330.928.2155

The Innovators of Quality Framing and Lath Systems

EXPANDED DIAMOND METAL LATH SPECIFICATION



| Wt. Per Sq. Yd. | Sheet Size | Pcs. / Bdl. | Yds. / Pallet |
|-----------------|-------------------|-------------|---------------|
| 1.75 lbs. | 27" x 96" | 10 | 1000 |
| 2.50 lbs. | 27" x 96" | 10 | 1000 |
| 3.40 lbs. | 27" x 96" | 10 | 1000 |

50 bundles per pallet

CEMCO Expanded Diamond Metal Lath is a versatile metal lath ideal as a plaster base and reinforcement for all types of walls, ceilings and fireproofing of steel beam, and columns. Easy to cut and form to ornamental plaster work. Provides ample keying for scratch coat and is commonly used for plaster machine application. This lath is produced in either ASTM A653 hot dipped galvanized steel with a minimum G60 coating or zinc coated carbon steel. This lath meets the following specifications:

Federal Specification - QQ-L-101C American National Standard Specification - ANSI A42.3 and A42.4 American Society for Testing Materials - ASTM C841 and ANSI/ASTM C847 U. S. Department of Housing and Urban Development (HUD) Standards 4930.1 Uniform Building Code, 2001 Calif. Bldg Code, 2003 IBC - Chapter 25 For further information see ICBO ES Report No. 4120

CALIFORNIA EXPANDED METAL LATH PRODUCTS CO.

Corporate Office 263 N. Covina Lane, City of Industry, CA 91744 Phone (800) 775-2362 Fax (626) 330-7598

1001-A Pittsburg Antioch Hwy, Pittsburg, CA 94565 Phone (925) 473-9340 Fax (925) 473-9341 490 Osage Street, Denver, CO 80204 Phone (303) 572-3626 Fax (303) 572-3627